

# Beam monitors Mechanical integration

Ioannis Apostolidis
Detector Group mechanical engineer





		Bunker			Guides-Choppers		Sample	
1. ESTIA	Original config	10.7m	11.1m				23m – Pre sample	
	Current config	10.7m	11.1m				23m – Pre sample	
2. SKADI	Original config	6m					Sample incident	Transmission
	Current config	9m			15.5m		Pre sample	Transmission
3. VESPA	Original config	7.44m	10m		20m		Sample incident	
	Current config	7.38m	10.02m		20.02m		58.37m – Pre sample	59.6m - Transmission
4. ODIN	Original config	8.42m	13.2m		33m		Sample incident	
	Current config	8.42m	23.7m				53m – Pre sample	
5. DREAM	Original config	6.175m	9.78m				Sample incident	
	Current config	6.6m	10.3m				Pre sample	Transmission
6. NMX	Original config	BBG					Sample incident	
	Current config	BBG					Sample incident	
7. BEER	Original config	8.3m	9.875m				Pre sample	
	Current config	6.44m	9.875m				Pre sample (by HZG)	
8. CSPEC	Original config	Mod flux			105.6m		158.5m – Pre sample	Transmission
	Current config	6m			28m	105.6m	160m – Pre sample	Transmission (TBD)
9. BIFROST	Original config	8.25m					Pre sample	
	Current config	6.9m			27.9m	80.1m	Pre sample + Braggs peak	Transmission
10.MIRACLES	Original config	7.8m					162.2m – Pre sample	
	Current config	8.3m			54.6m		162.2m – Pre sample	163m - Transmission
11.MAGIC	Original config	6.7m					Sample incident	
	Current config	6.8m					Pre sample	
12.TREX	Original config	6m			108m		162m – Pre sample	Transmission
	Current config	6m			108m		162m – Pre sample	Transmission
13.HEIMDAL	Original config	8.1m	20m				Pre sample	
	Current config	8.1m	20m				Pre sample	
14.FREIA	Original config		8.3m	10.3m	16.25m		Sample incident	
	Current config	6.8m	8.8m		14.9m	17.9m	22.4m – Pre sample	
15.LOKI	Original config	6.5m					Sample incident	Transmission Transmission
	Current config	6.5m			15.5m		Pre sample	Transmission (snout) Transmission (beam stop)

#### Bunker integration workshop




#### Issues discussed:


- Remote handling classification Decide where BM is integrated on an existing RH module or creates its own
- Crane access
- Preamp box location
- Cable routing
- Ease of mounting/dismounting
- Use of standard RH components
- Keep maintenance to a minimum
- Thanks to Erik Nilsson!

#### **Bunker Crane access**




















### Generic cabling configuration - 2






#### Generic cabling configuration – 2a




#### Generic configuration BM - preamp






- BM to Preamp cable length: <2m</li>
- Height of Preamp box similar to cable tray level



Spatial envelope in X-Y to be considered for shielding and mounting purposes








ODIN CAD – Elbio Calzada

- Height level of preamp box similar to cable tray mount on tray if possible
- Consider:
  - Routing the cable with chopper's
  - BM is mounted on Chopper RH module

#### Specific examples – BIFROST






BIFROST CAD - Liam Whitelegg


- Height level of pre-amp similar to cable tray
- Want to mount on to cable tray if possible
- BM is mounted on Chopper RH module

#### Specific examples – NMX





- Height level of pre-amp similar to cable tray
- Want to mount on to cable tray if possible
- Challenges:
  - Crane access
  - Tool access
  - How to get everything in/out
  - Which is the RH module?



NMX CAD – Giuseppe Aprigliano

#### Moving forward



- Already in contact with companies for vacuum compatible BMs
- Receive further considerations from instruments
- Detailed design on case by case basis once an instrument is signed up to project



## Thank you!